

Switching Power Supply

Model : SW-Series

Switching Power Supply สำหรับงานอุตสาหกรรม ขนาดเล็ก กำลังไฟสูง
มี 2 รุ่นใหม่ ล่าสุด ให้เลือกใช้ Model : SW-20A12 (12V 20A) และ

Model : SW-10A24 (24 V 10 A)

พร้อมเงื่อนไขการรับประกัน 1 ปี ทุกรุ่น

มีอะไหล่สำรองซ่อมตลอดอายุการใช้งาน



Technical Specifications

AC Input Voltage range	170-264 VAC , 47-63 Hz.
Input Current	2.5A /230V
AC inrush current	50A/230V
Leakage current	<3.5mA /240VAC
DC adjustable range	+/-10% rated output voltage
Over load protection	105 - 135% hiccup mode, auto-recovery
Over-voltage protection	115-135% Cut-off the output, auto-recovery
Over-temp protection	rectifier >90°C cut-off the output, auto-recovery
Setup rise hold up time	200ms 100ms 20ms
Withstand voltage	I/P-O/P:1.5KvAC 1 minute I/P-FG:1.5KvAC 1 minute O/P-FG:0.5KvAC 1 minute
Working temperature	-20°C to +60°C, 20% to 90% RH
Dimension	W71 x L223 x H39 mm
Weight	0.66 kg.

Model	Output	Error	Range	Efficiency
SW-20A12	12V,0-20A	+/-1%	150mV	80%
SW-10A24	24V,0-10A	+/-1%	150mV	84%